

February 2011

## Product

Hef-T-Foot™

## Features

The Hef-T-Foot™ supports small pipework and runs of cable tray, and can also be used to mount a/c condensing units, air source heat pumps and a variety of outdoor equipment.

### Hef-T-Foot™ with steel strut

Available in four sizes 250mm, 400mm, 600mm, and 1000mm supplied with 41mmx21mm galvanised steel strut pre-adhered to the rubber.

### Hef-T-Foot™ universal

Supplied with three M10 threaded inserts moulded into the rubber. Available in one standard size 250mm.



	Material
Rubber	Compression moulded using milled, sieved and graded, recycled rubber bound with high quality adhesive. Density 1.0g/cm <sup>3</sup> . Working temperature range -10°C to 75°C (14°F to 167°F).
Strut	41mm x 21mm x 1.5mm (1.6" x .83" x .06") galvanised steel
Inserts	M10 (metric course thread) x 20mm/.79", zinc plated steel, through inserts. Maximum torque 15Nm. Maximum load 25kg/55lbs.

Part Code	Description	Length	Width	Height	Weight	Max. Load
FF-250-S	Hef-T-Foot 250mm/9.84" Strut	250mm/9.84"	185mm/7.28"	100mm/3.94"	2.8kg/6.2lbs	125kg/275lbs
FF-400-S	Hef-T-Foot 400mm/15.75" Strut	400mm/15.75"	185mm/7.28"	100mm/3.94"	4.6kg/10.1lbs	200kg/440lbs
FF-600-S	Hef-T-Foot 600mm/23.62" Strut	600mm/23.62"	185mm/7.28"	100mm/3.94"	7.6kg/16.7lbs	300kg/660lbs
FF-1000-S	Hef-T-Foot 1000mm/39.37" Strut	1000mm/39.37"	185mm/7.28"	100mm/3.94"	12kg/26.4lbs	500kg/1100lbs

Part Code	Description	Length	Width	Height	Weight	Max. Load
FF-250-UNI	Hef-T-Foot 250mm/9.84" Universal	250mm/9.84"	185mm/7.28"	100mm/3.94"	2.8kg/6.2lbs	125kg/275lbs