# For Residential and Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

# **Series FH**

# Frost-proof Automatic Draining Wall Hydrants

Sizes: 1/2" x 1/2", 3/4" x 1/2", 3/4" x 3/4"

Series FH Frost-proof Automatic Draining Wall Hydrants are designed to provide freeze protection for external water supply.

#### **Features**

- Self drains automatically
- Positive seat water shut-off
- 3/4" hose outlet

#### Models

FH-1-M1


For wall sizes: 4" - 14", ½" solder or ½" male IPS inlet.


FH-1-M1-PEX

For wall sizes: 4" - 14",  $\frac{1}{2}"$  PEX inlet.

### **Specifications**

A frost-proof automatic draining wall hydrant to be installed where indicated in the plans. Hydrant to be manufactured of a nickel-plated brass body with a metal handle. Plastic handles are not acceptable. Hydrant to be either solder, IPS, or PEX inlet by  $^3\!4$ " hose outlet. Hydrant to be a Watts Series FH.





## **Dimensions - Weights**

MODEL	SIZE	DIMENSIONS				WEIGHT		
		Α		В				
	in.	in.	mm	in.	mm	lbs.	kgs	
Inlet ½" solder or ½" male IPS								
FH-1-M1	4	4 <sup>15</sup> / <sub>16</sub>	125	315/32	88	0.93	0.42	
FH-1-M1	6	7	178	315/32	88	1.00	0.45	
FH-1-M1	8	8	203	315/32	88	1.05	0.48	
FH-1-M1	10	11	279	315/32	88	1.08	0.49	
FH-1-M1	12	13	330	315/32	88	1.13	0.51	
FH-1-M1	14	15	381	315/32	88	1.20	0.54	
Inlet ½" PEX								
FH-1-M1-PEX	4	5½	140	315/32	88	0.93	0.42	
FH-1-M1-PEX	6	71/2	191	315/32	88	1.00	0.45	
FH-1-M1-PEX	8	81/2	216	315/32	88	1.05	0.48	
FH-1-M1-PEX	10	11½	293	315/32	88	1.08	0.49	
FH-1-M1-PEX	12	13½	344	315/32	88	1.13	0.51	
FH-1-M1-PEX	14	15½	395	315/32	88	1.20	0.54	

#### NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



**USA:** T: (978) 689-6066 • F: (978) 975-8350 • Watts.com **Canada:** T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca **Latin America:** T: (52) 81-1001-8600 • Watts.com

ES-FH 1139 © 2011 Watts