

For Residential and Light Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Series PWFCTTM

Top Mount Faucets

Size: 3/8" (10mm)

Features

- Top mount design – you'll never need to crawl below the sink again!
- Reduces installation labor
- Components touching water are stainless steel or non-metallic
- Wide range of finishes, including chrome, brushed nickel, oil rubbed bronze, white & black
- Models with filter change monitors are available to remind customers when to change cartridges for water quality assurance
- Ceramic disc for durability
- One style works for air gap and non-air gap installations
- NSF certified for material requirements

PURE WATER



Top mount faucets available in wide range of finishes.



Models with monitors are available.

Top Mount Faucet Models

MODEL NO.	FINISH	INSTALLATION TYPE	TUBING SIZE	FILTER CHANGE MONITOR
PWFCTTMMCH	Chrome	Air gap or non air gap	3/8"	Yes
PWFCTTMCH	Chrome	Air gap or non air gap	3/8"	No
PWFCTTMMBN	Brushed Nickel	Air gap or non air gap	3/8"	Yes
PWFCTTMBN	Brushed Nickel	Air gap or non air gap	3/8"	No
PWFCTTMMWH	White	Air gap or non air gap	3/8"	Yes
PWFCTTMWH	White	Air gap or non air gap	3/8"	No
PWFCTTMMBK	Black	Air gap or non air gap	3/8"	Yes
PWFCTTMBK	Black	Air gap or non air gap	3/8"	No
PWFCTTMMOB	Oil Rubbed Bronze	Air gap or non air gap	3/8"	Yes
PWFCTTMOB	Oil Rubbed Bronze	Air gap or non air gap	3/8"	No

Fittings for 1/4" connections available. Please inquire.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

Installation



Install Tubing

Watts top mount faucets come with quick connect fittings for both air gap and non-air gap installations. To start the installation process, install tubing for feed water and air gap connections, if an air gap is to be used.



Install Faucet

- Place the O-ring (provided) around the hole, drilled in the counter top.
- Working from the top, push tubing through the hole in the counter top;
- Squeeze the wings of the toggle bolt so it drops through the hole in the counter top.



Secure Faucet To Counter Top

Finally, remove spout from faucet, and tighten the Phillips head screw inside the faucet with a Phillips head screwdriver.

The top mount faucet installation is now complete, without the need to crawl below the sink!

Monitor faucets eliminate guesswork and remind customers when cartridge replacements are necessary to provide top water quality assurance!

How they work:

- Monitors track time and estimate gallons based on time.
- LED flashes red after six months or after it estimates 2,000 gallons of water have been used by the system.
- Each time cartridges are replaced a new battery is recommended.
- New battery will reset the monitor and LED indicator is again blue.

Battery Replacement: WTMFBAT



**Two Faucet Types
Monitor and Standard**



**Faucet with battery operated
Filter change monitor**



**Certified by NSF International
against NSF/ANSI Standard 42
for material requirements.**

WATTS®

A Watts Water Technologies Company



USA: Tel. (800) 224-1299 • www.watts.com
Canada: Tel. (888) 208-8927 • www.watts.ca